

DESTAC VEG

NONSTICK VEGETABLE-BASED

DESCRIPTION

Biodegradable liquid fluid based on vegetable oil.

APPLICATIONS

DESTAC VEG is a non-adhering fluid specifically developed to replace petroleum source solvents.

DESTAC VEG is used as a non-adhering coating for the transport and application of road asphalt. It can also be used for wood sawing or other applications where a biodegradable oil is required.

The product can be applied by spray, pressure and other means.

PROPERTIES

- Non-toxic.
- Easily biodegradable.
- VOC: 0 %.
- High flashpoint.
- Preserves asphalt mix.
- Compatible with plastics.
- Weak odour.

TECHNICAL CHARACTERISTICS

	Method	Typical values	Units
Appearance	clear		
Density at 15°C.	ASTM D-1298	0,91	gr/cm ³
Viscosity at 40°C.	ASTM D-445	22	cSt
Viscosity Index	ASTM D-2270	> 200	-
Pour point	ASTM D-97	-21	°C
Flash point	ASTM D-92	> 160	°C

Rev: 05/21

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.
COGELSA is not liable for damages caused by improper use of the product.