

ULTRADEG 65

DEGREASING AGENT

DESCRIPTION

ULTRADEG 65 is a mixture of synthetic hydrocarbons. The product is colorless, transparent and odorless. It is an all-round cleaner for easy removal of dirt, oil, grease and resin, always used cold.

APPLICATION

ULTRADEG 65 is used for cleaning and degreasing engines, landing gears, machines, tools, etc. The product is also used for degreasing industrially manufactured components. It does not contain aromatic substances, chlorine or HCFC.

ULTRADEG 65 has been specially formulated to evaporate without leaving any residues.

Certified by NSF C1, Registration No. 149232 for use in the food industry.

HALAL Certification, nº IH-682/2.4/B/76/1/7

KOSHER Certification



PROPERTIES

ULTRADEG 65 has a high volatility (Evaporation index 100 / Ether ethyl reference 1). The product does not leave any residues as it is based on a mixture of specially selected synthetic solvents.

HOW TO USE

ULTRADEG 65 cleaner can be applied by spray gun, brush or sponge. It should be used pure.

QUALITY LEVEL

TECHNICAL CHARACTERISTICS

| | Units | Typical values | Method |
|--------------------|--------------------|------------------------|-------------|
| Appearance | - | Transparent, colorless | - |
| Density at 15 °C | kg/dm ³ | 0,76 | ASTM D 1298 |
| Viscosity at 40 °C | cSt | 1,0 | ASTM D 445 |
| Flash point | °C | > 61 | ASTM D 93 |
| Pour point | °C | < -23 | ASTM D 97 |

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.

ULTRADEG 65

DEGREASING AGENT

HANDLING AND STORAGE

Handling not subject to special requirements. Throughout the lifespan of the product:

- Store separately from other lubricants, chemicals or foodstuffs.
- Protect from sunlight or other heat sources.
- Store at temperatures from 1°C up to +40°C.
- Keep container closed after opening.

The expiry date is 48 months from date of manufacture.

For further information and more product details, packaging and safety data sheets, please refer to our website www.cogelsa.com or contact us at: info@cogelsa.com or export@cogelsa.com

Rev: 11/23

The information provided in this document is based upon our best knowledge at the date of revision indicate, and is subject to changes without prior notice. Such information does not release the user from testing the product in their own application. The data indicated represent average values and do not constitute product specifications. For more information please contact COGELSA Technical Support.

COGELSA is not liable for damages caused by improper use of the product.